

## Specification sheet

# AWFIK-1035-E ECOMIX Multifilter

<b>Capacity nominal/peak:</b>	1,2 m <sup>3</sup> /h / 1,5 m <sup>3</sup> /h
<b>Volume of filter media:</b>	25 L
<b>Volume capacity (for hardness at 15 °dH):</b>	3,5 m <sup>3</sup>
<b>Salt consumption/regeneration:</b>	2,5...4,0 Kg
<b>Water consumption/regeneration (volume of discharge):</b>	0,25 m <sup>3</sup>
<b>Regeneration duration:</b>	80...110 min
<b>Pressure drop in service mode:</b>	0,5...1,0 bar
<b>Operating pressure:</b>	2...6 bar
<b>Power supply:</b>	230 VAC, 50 Hz
<b>Power consumption:</b>	30 W
<b>Connections, main water:</b>	1" O.D
<b>Net weight:</b>	30 Kg
<b>Dimensions (height x width x depth):</b>	113 x 35 x 52 cm

### *Feed Water Requirements*

<b>Temperature, feed water:</b>	+4 ... 30°C
<b>COD:</b>	>20 mg/l
<b>Hardness:</b>	>42 °dH
<b>Iron:</b>	>15 mg/l
<b>Manganese:</b>	>3 mg/l
<b>Ammonium:</b>	>4 mg/l
<b>Required level of pre-purified water from sediments:</b>	100 micron



**Part number:**

**AWFIK-1035-E**